Sky Brightness Analysis using a Million Ground-Based Electro-Optical Deep Space Surveillance (GEODSS) Observations

W. Jody Mandeville, Norman Facas, Tim McLaughlin, Steve Six

The MITRE Corporation

Alan Garner
AFLCMC/HBQS

CONFERENCE PAPER

Brightness of the sky background due to lunar phase and location can dramatically affect the limiting magnitude of astronomical detectors. Formerly, theoretical models have attained limited data sets with 10-20% differences between model and observation. This paper compares and contrasts previous investigations with over a million data points collected from various GEODSS sites located around the world, and attempts to refine predictive modeling of sky brightness for use in scheduling, as well as modeling and simulation tools.

1. INTRODUCTION

In this paper we analyze a vast number of sky brightness observations from the United States Air Force's three Ground-Based Electro-Optical Deep Space Surveillance (GEODSS) sites with the goal of increasing the fidelity of our modeling and simulation software. The GEODSS system is comprised of three facilities located in Socorro, New Mexico; Maui, Hawaii; and Diego Garcia, British Indian Ocean Territory. Each GEODSS telescope uses a 1 meter primary mirror and highly sensitive digital camera known as Deep STARE.[1] The data available to us for this study includes nearly a million data points each with date and time of observation, measured sky brightness at the sky location of observation, and atmospheric extinction coefficient. From the date and time for each observation we determine the phase and location of the moon relative to the observation. For this report we are specifically interested in determining the change in the visual magnitude of background dark sky based on the relative position and phase of the moon. Reasonably straight forward physics based algorithms have been presented in the literature by Krisciunas and Schaefer with a reported 23% accuracy.[4] With our large statistical sampling we endeavor to improve the fit of these equations to our data by adding a bias factor to one of our measured parameters.

2. BACKGROUND

The following equation, as derived by Krisciunas and Schaefer, represents the change in visual magnitude caused by contributions of scattered moonlight[4]:

$$\Delta V = -2.5 \log[(B_{moon} + B_0(Z))/B_0(Z)], \tag{1}$$

where

$$B_0(Z) = B_{zen} 10^{-0.4k(X-1)} X, (2)$$

$$B_{moon} = f(\rho)I^*10^{-0.4kX(Z_m)}[1 - 10^{-0.4kX(Z)}], \tag{3}$$

$$I^* = 10^{-0.4(3.84 + 0.026|\alpha| + 4 \times 10^{-9}\alpha)},\tag{4}$$

$$f(\rho) = 10^{5.36} [1.06 + \cos^2(\rho)] + 10^{6.15 - \rho/40}, \tag{5}$$

$$X(Z) = (1 - 0.96\sin^2 Z)^{-0.5}. (6)$$

The input parameters required for these equations are lunar phase angle α , moon/sky separation ρ , extinction coefficient k, zenith distance of the moon Z_m , and zenith distance of the sky position Z. The only value

| including suggestions for reducing | completing and reviewing the collect this burden, to Washington Headqu uld be aware that notwithstanding ar DMB control number. | arters Services, Directorate for Infor | mation Operations and Reports | , 1215 Jefferson Davis | Highway, Suite 1204, Arlington | | |
|--|--|---|------------------------------------|--|----------------------------------|--|--|
| 1. REPORT DATE SEP 2012 | 2. REPORT TYPE | | | 3. DATES COVERED 00-00-2012 to 00-00-2012 | | | |
| 4. TITLE AND SUBTITLE | | 5a. CONTRACT NUMBER | | | | | |
| Sky Brightness Analysis using a Million Ground-Based Electro-Optical Deep Space Surveillance (GEODSS) Observations | | | | | 5b. GRANT NUMBER | | |
| Deep Space Survei | liance (GEODSS) O | 5c. PROGRAM ELEMENT NUMBER | | | | | |
| 6. AUTHOR(S) | | 5d. PROJECT NUMBER | | | | | |
| | | 5e. TASK NUMBER | | | | | |
| | | 5f. WORK UNIT NUMBER | | | | | |
| | ZATION NAME(S) AND AC Dration,202 Burlingt | 8. PERFORMING ORGANIZATION REPORT NUMBER | | | | | |
| 9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES) | | | | | 10. SPONSOR/MONITOR'S ACRONYM(S) | | |
| | | 11. SPONSOR/MONITOR'S REPORT NUMBER(S) | | | | | |
| 12. DISTRIBUTION/AVAIL Approved for publ | LABILITY STATEMENT ic release; distributi | on unlimited | | | | | |
| 13. SUPPLEMENTARY NO In Advanced Maui Maui, HI. | Optical and Space | Surveillance Techno | ologies Conferenc | e (AMOS), 1 | 1-14 Sep 2012, | | |
| 14. ABSTRACT | | | | | | | |
| 15. SUBJECT TERMS | | | | | | | |
| 16. SECURITY CLASSIFIC | 17. LIMITATION OF ABSTRACT | 18. NUMBER OF PAGES | 19a. NAME OF RESPONSIBLE PERSON | | | | |
| a. REPORT unclassified | b. ABSTRACT unclassified | c. THIS PAGE unclassified | Same as Report (SAR) | 5 | RESPONSIBLE PERSON | | |

Public reporting burden for the collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and

Report Documentation Page

Form Approved OMB No. 0704-0188 required for calculating ΔV that we do not get directly from our data is the dark zenith sky brightness B_{zen} . To convert between linear brightness values (B) in nanoLamberts and logarithmic visual magnitudes per square arc second (V) we use [2]

$$B = 34.08e^{(20.7233 - 0.92104V)}. (7)$$

In the following section we discuss the processing of our data and compare the theoretical values predicted by Eqn. 1 and our measured data. Additionally we discuss a modification we make to reduce the error between the predicted and measured values which gives us better agreement between our simulations and measured data.

3. RESULTS/DISCUSSION

GEODSS sites operate during twilight to maximize data collection time. For our analysis the data collected during twilight has added background brightness that we are not accounting for in this analysis so we choose to remove this data. Data from the Maui site collected over a 10 day period is shown in Fig. 1. We manually remove the twilight data as indicated in the figure.






Figure 1: Data acquired by the Maui GEODSS site over a ten day period. Local sunrise and sunset are indicated on the graph. Twilight data that is circled was removed for the analysis presented in this paper.

Once the twilight data is removed we separate out the data for each site collected when there is no moon in the sky. We use this "moonless" data to calculate a median dark sky visual magnitude. The value for the dark sky visual magnitude for each site is used in Eqn. 7 to find B_{zen} . We then use Matlab[®] to perform an optimized fit for ΔV . The optimization algorithm we use minimizes the mean squared error (MSE). The histograms for the errors for each of the GEODSS sites is shown in Fig. 2a. The value for MSE for Socorro, Maui, and Diego Garcia is 0.324, 0.518, and 0.462 respectively. The asymmetric nature of these histograms is an indication that we may not be accounting for one or more systematic sources of error. We acknowledge that we are not accounting for some sources of sky brightness to include galactic latitude[5] of our observation as well as fluctuations in solar brightness[3].

In an attempt to keep our modeling and simulation algorithms relatively simple we choose to apply an empirical bias factor to B_{zen} as opposed to using more complicated algorithms that take secondary effects such as galactic latitude and solar activity level into account. In doing this we break the connection between V and B_{zen} given by Eqn. 7. When we allow these two variables to be optimized independently by the fitting function we arrive at a fit that is an average of 32% better. The most significant change is for the data from Maui which is more than 50% better according to this metric. The new MSE values are 0.268, 0.240, and 0.344 for Socorro, Maui, and Diego Garcia respectively. The fitting results are shown in Table 1. The columns labeled V, B_{zen} and MSE are the results from directly using Eqns. 1-6 whereas the last two columns





- (a) The fitting parameter for this set of histograms is the dark zenith sky brightness B_{zen} .
- (b) The fitting parameters for this set of histograms are the dark zenith sky brightness B_{zen} and ΔV .

Figure 2: Histograms of the error between theory and data for the three GEODSS sites located at Socorro, NM; Maui, Hawaii; Diego Garcia from top to bottom respectfully in each figure.

represent the values where we allow B_{zen} to vary independently from V. We call these new values B_{zen}^{\star} and MSE^{*}. For completeness we include the average extinction coefficient k from our data which we used for these fits. Using this two parameter fitting approach, we arrive at a fairly simple empirical equation that

Table 1: Fitting Parameters

| Site | k | V | B_{zen} | MSE | B_{zen}^{\star} | MSE* |
|--------------|------|-------|-----------|-------|-------------------|-------|
| Socorro | 0.60 | 21.11 | 122.59 | 0.324 | 165.82 | 0.268 |
| Maui | 0.54 | 21.35 | 98.28 | 0.518 | 224.18 | 0.240 |
| Diego Garcia | 0.34 | 21.10 | 123.73 | 0.462 | 199.89 | 0.344 |

can be used in our modeling and simulation work. The blue dots shown in Fig. 3 are calculated using this equation, while the black dots represent measured data from the Socorro GEODSS site. The ten subfigures show the value of ΔV for different lunar phases. The data and fits from Maui and Diego Garcia show similar agreement.

4. CONCLUSION

In conclusion we feel that by using Krisciunas' and Schaefer's equations with the addition of a small bias factor for B_{zen} , we achieve nice agreement between predictions and measured data for the brightness of the night sky as a function of lunar phase and location. The addition of this algorithm to our modeling and simulation software allows us to further enhance the fidelity of our results.

We would like to thank the Electronics Systems Center's HSIJ program office and the Executive Agent for Space (EA4S) for continued support of our modeling and simulations efforts.




Figure 3: Comparison of simulated results and data collected from the Socorro, NM GEODSS site. Each subfigure shows a different moon phase α .

5. REFERENCES

- [1] US Air Force. USAF Fact Sheet: Ground-based electro-optical deep space survillance. http://www.af.mil/information/factsheets/factsheet_print.asp?fsID=170&page=1, July 2012.
- [2] R. H. Garstang. Night-sky brightness at observatories and sites. Astronomical Society of the Pacific, 101:306–329, March 1989.
- [3] K. Krisciunas. Optical night-sky brightness at mauna kea over the course of a complete sunspot cycle. *Astronomical Society of the Pacific*, 109:1181–1188, October 1997.
- [4] K. Krisciunas and B. E. Schaefer. A model of the brightness of moonlight. *Astronomical Society of the Pacific*, 103:1033–1039, September 1991.
- [5] R. C. Stone, D. G. Monet, A. K. B. Monet, F. H. Harris, H. D. Ables, C. C. Dahn, B. Canzian, H. H. Guetter, H. C. Harris, A. A. Henden, S. E. Levine, C. B. Luginbuhl, J. A. Munn, J. R. Pier, F. J. Vrba, and R. L. Walker. Upgrades to the Flagstaff Astrometric Scanning Transit Telescope: A Fully Automated Telescope for Astrometry. *The Astronomical Journal*, 126:2060–2080, October 2003.